DIGITAL GAS FLOWMETER



Spink Controls Gas Flowmeter specifically designed to measure the flow of clean gases non-corrosive to silicon. The physical pressure is measured to piezoresistive pressure sensing element where the pressure is converted into a differential voltage signal which is almost proportional to the pressure. This differential voltage is corrected and conditioned in multiple steps, and derive the flow of the gas.

TECHNICAL SPECIFICATION

TYPE : DIFFERENTIAL TYPE

ACCURACY : +/- 1% of FSR

RANGEABILITY : 20:1
REPEATABILITY : +/- 0.25%
PRESSURE RATING : 2 BAR
TEMPERATURE RATING : 70°C
DP : 1 PSI

MOC : SS 304/SS 316

FLOW DIRECTION : HORIZONTAL / VERTICAL

POWER SUPPLY : 18 – 30 VDC

OUT PUT : 2 WIRE LOOP POWERED

ENCLOSURE : FLAMEPROOF / WEATHERPROOF

LINE SIZE : ½" to 1"



Head Office

303, SIDDHARTH TOWER, MYNOOMAL PATH,KOPRI, THANE(E) - 400 603 MAHARASHTRA, INDIA

Fax : +91 22 2532 4845 Phone : +91 22 2532 8223 +91 22 2532 8224

Email: info@spinkcontrolsindia.com

Hydrabad Office

Plot No. 108, Flat No. 201 Jyoti Residency, KNR Colony, Nizampet Village Kukatpally Hyderabad - 500090 INDIA Phone: +91 8977269867

Email: spinkcontrolhyderabad@gmail.com

Plant

GALA No. F-4 A WING, UDYOG BHAVAN-2 ADDITIONAL AMBERNATH, INDUSTRIAL AREA, ANADO NAGAR MIDC AMBERNATH,

Dist - THANE 421501

Phone : +91 9594991196

Email : rupa.thakkar@spinkcontrols.com